

MASHT SERIES / 292mm

EN 779 EFFICIENCY: M6-F9
 MEDIA : Micro Glass Fibre
 SEPARATORS: Corrugated Aluminum
 FRAME: Galvanized Steel
 PROTECTION GRID: Galvanized Steel on both sides
 FINAL PRESSURE DROP: 450 Pascals
 OPERATING TEMPERATURE: 350 °C

CODE DESIGNATION:
 1H: SINGLE HEADER
 2H: DOUBLE HEADER



MASHT FILTERS

Part Number	Filter Class (EN 779)	Width (mm)	Height (mm)	Depth (mm)	Media Area (m ²)	Air Flow (m ³ /h)	Pressure drop (Pascals)	Energy Rating
M6								
MASHT-287/592/292-6GD2G1H	M6	287	592	292	4,5	1700	110	E
MASHT-492/592/292-6GD2G1H	M6	492	592	292	7,5	2500	110	E
MASHT-592/592/292-6GD2G1H	M6	592	592	292	9,0	3400	110	E
MASHT-287/592/292-6GD2G1H-6	M6	287	592	292	6,0	1700	110	E
MASHT-492/592/292-6GD2G1H-9	M6	492	592	292	9,0	2500	110	E
MASHT-592/592/292-6GD2G1H-12	M6	592	592	292	12,0	3400	110	E
MASHT-305/610/292-6GD2G	M6	305	610	292	6,0	2125	130	D
MASHT-490/610/292-6GD2G	M6	490	610	292	9,0	3400	130	D
MASHT-610/610/292-6GD2G	M6	610	610	292	12,0	4250	130	D
MASHT-305/610/292-6GD2G-7	M6	305	610	292	7,0	2125	130	D
MASHT-490/610/292-6GD2G-11	M6	490	610	292	11,0	3400	130	D
MASHT-610/610/292-6GD2G-14	M6	610	610	292	14,0	4250	130	D

F8								
MASHT-287/592/292-8GD2G1H	F8	287	592	292	4,5	1700	150	D
MASHT-492/592/292-8GD2G1H	F8	492	592	292	7,5	2500	150	D
MASHT-592/592/292-8GD2G1H	F8	592	592	292	9,0	3400	150	D
MASHT-287/592/292-8GD2G1H-6	F8	287	592	292	6,0	1700	150	D
MASHT-492/592/292-8GD2G1H-9	F8	492	592	292	9,0	2500	150	D
MASHT-592/592/292-8GD2G1H-12	F8	592	592	292	12,0	3400	150	D
MASHT-305/610/292-8GD2G	F8	305	610	292	6,0	2125	160	C
MASHT-490/610/292-8GD2G	F8	490	610	292	9,0	3400	160	C
MASHT-610/610/292-8GD2G	F8	610	610	292	12,0	4250	160	C
MASHT-305/610/292-8GD2G-7	F8	305	610	292	7,0	2125	160	C
MASHT-490/610/292-8GD2G-11	F8	490	610	292	11,0	3400	160	C
MASHT-610/610/292-8GD2G-14	F8	610	610	292	14,0	4250	160	C