

MHH MICRO-HOOD TERMINAL HEPA / ULPA FILTER MODULS / 125mm

EN 1822 EFFICIENCY:

MEDIA :

SEPARATORS:

PROTECTION GRIDS:

GASKET:

RECOMMENDED FINAL,

PRESSURE DROP:

OPERATING TEMPERATURE: 80 °C degrees

Micro Glass Fibre
Hotmelt
Painted Aluminum on,
both sides
Two component
continuous,
polyurethane

600 Pascals



MICRO-HOOD TERMINAL HEPA / ULPA FILTER MODULS

Part Number	Filter Class (EN 1822)	Width (mm)	Height (mm)	Depth (mm)	Collar (mm)	Media Area (m ²)	Air Flow (m ³ /h) (0,45m/s)	Pressure drop (Pascals)
H13								
MHH-610/610/125-B200-13AD2G	H13	610	610	125	200	10,4	600	125
MHH-610/915/125-B200-13AD2G	H13	610	915	125	200	15,6	900	125
MHH-610/1220/125-B200-13AD2G	H13	610	1220	125	200	20,8	1200	125
H14								
MHH-610/610/125-B200-14AD2G	H14	610	610	125	200	10,4	600	135
MHH-610/915/125-B200-14AD2G	H14	610	915	125	200	15,6	900	135
MHH-610/1220/125-B200-14AD2G	H14	610	1220	125	200	20,8	1200	135
U15								
MHH-610/610/125-B200-15AD2G	U15	610	610	125	200	10,4	600	155
MHH-610/915/125-B200-15AD2G	U15	610	915	125	200	15,6	900	155
MHH-610/1220/125-B200-15AD2G	U15	610	1220	125	200	20,8	1200	155