

MPF SERIES / 150mm - 292mm

EN 779 EFFICIENCY: M6-F9
MEDIA : Micro Glass Fibre
SEPARATORS: Hotmelt
FRAME: Galvanized Steel, Aluminum, Stainless Steel, MDF, Plastic
PROTECTION GRID: Expanded Galvanized Steel
GASKET: Two component, continuous polyurethane
FINAL PRESSURE DROP: 450 Pascals
OPERATING TEMPERATURE: 80 °C



MPF FILTERS

Part Number	Filter Class (EN 779)	Width (mm)	Height (mm)	Depth (mm)	Media Area (m ²)	Air Flow (m ³ /h)	Pressure drop (Pascals)
M6 ▶							
MPF-287/592/48-6GN	M6	287	592	48	3,0	1000	65
MPF-492/592/48-6GN	M6	492	592	48	5,0	1600	65
MPF-592/592/48-6GN	M6	592	592	48	6,0	2000	65
MPF-287/592/96-6GN	M6	287	592	96	5,5	1450	80
MPF-492/592/96-6GN	M6	492	592	96	9,0	2400	80
MPF-592/592/96-6GN	M6	592	592	96	11,0	2900	80
F7 ▶							
MPF-287/592/48-7GN	F7	287	592	48	3,0	1000	80
MPF-492/592/48-7GN	F7	492	592	48	5,0	1600	80
MPF-592/592/48-7GN	F7	592	592	48	6,0	2000	80
MPF-287/592/96-7GN	F7	287	592	96	5,5	1450	90
MPF-492/592/96-7GN	F7	492	592	96	9,0	2400	90
MPF-592/592/96-7GN	F7	592	592	96	11,0	2900	90
F8 ▶							
MPF-287/592/48-8GN	F8	287	592	48	3,0	1000	100
MPF-492/592/48-8GN	F8	492	592	48	5,0	1600	100
MPF-592/592/48-8GN	F8	592	592	48	6,0	2000	100
MPF-287/592/96-8GN	F8	287	592	96	5,5	1450	105
MPF-492/592/96-8GN	F8	492	592	96	9,0	2400	105
MPF-592/592/96-8GN	F8	592	592	96	11,0	2900	105

MPF FILTERS

Part Number	Filter Class (EN 779)	Width (mm)	Height (mm)	Depth (mm)	Media Area (m ²)	Air Flow (m ³ /h)	Pressure drop (Pascals)	Energy Rating
F9 ▶								
MPF-287/592/150-9GN	F9	287	592	150	7,50	1700	150	B
MPF-492/592/150-9GN	F9	492	592	150	12,50	2800	150	B
MPF-592/592/150-9GN	F9	592	592	150	15,0	3400	150	B
MPF-287/592/292-9GN	F9	287	592	292	7,50	1700	150	B
MPF-492/592/292-9GN	F9	492	592	292	12,50	2800	150	B
MPF-592/592/292-9GN	F9	592	592	292	15,0	3400	150	B