

MPR COARSE POCKET FILTER SERIES / PLASTIC FRAME

EN 779 EFFICIENCY: G4-M6
 MEDIA : Rigid Polyester
 FRAME: Molded Plastic Frame
 FINAL PRESSURE DROP: 450 Pascals
 OPERATING TEMPERATURE: 80 °C



COARSE POCKET FILTERS WITH MOLDED PLASTIC FRAME

Part Number	Filter Class (EN 779)	Number of Pockets	Width (mm)	Height (mm)	Depth (mm)	Media Area (m ²)	Air Flow (m ³ /h)	Pressure drop (Pascals)	Energy Class
G4 ▶									
MPR-4-06600-03	G4	6	595	595	600	4,2	3400	45	-
MPR-4-03600-01	G4	3	287	595	600	2,1	1700	45	-
MPR-4-06360-03	G4	6	595	595	360	2,5	3400	50	-
MPR-4-03360-01	G4	3	287	595	360	1,2	1700	50	-
MPR-4-08600-03	G4	8	595	595	600	5,6	3400	45	C
MPR-4-04600-01	G4	4	287	595	600	2,8	1700	45	C
MPR-4-08360-03	G4	8	595	595	360	3,3	3400	50	D
MPR-4-04360-01	G4	4	287	595	360	1,6	1700	50	D
M5 ▶									
MPR-5-06600-03	M5	6	595	595	600	4,2	3400	45	C
MPR-5-03600-01	M5	3	287	595	600	2,1	1700	45	C
MPR-5-06360-03	M5	6	595	595	360	2,5	3400	55	E
MPR-5-03360-01	M5	3	287	595	360	1,2	1700	55	E
MPR-5-08600-03	M5	8	595	595	600	5,6	3400	45	A
MPR-5-04600-01	M5	4	287	595	600	2,8	1700	45	A
MPR-5-08360-03	M5	8	595	595	360	2,5	3400	55	E
MPR-5-04360-01	M5	4	287	595	360	1,2	1700	55	E
M6 ▶									
MPR-6-08600-03	M6	8	595	595	600	5,6	3400	50	C
MPR-6-04600-01	M6	4	287	595	600	2,8	1700	50	C