

MV4HT GALVANIZED SERIES / 292mm - 400mm

EN 779 EFFICIENCY: M6-F9
 MEDIA : Micro Glass Fibre
 SEPARATORS: Glass Fiber strip
 GASKET: Glass Fiber
 PROTECTION GRIDS: Galvanized Steel on both sides
 FRAME: Galvanized Steel
 FINAL PRESSURE DROP: 450 Pascals
 OPERATING TEMPERATURE: 350 °C



SILICONE FREE

MICROFIL V HIGH TEMPERATURE FILTERS

Part Number	Filter Class (EN 779)	Width (mm)	Height (mm)	Depth (mm)	Media Area (m ²)	Air Flow (m ³ /h)	Pressure drop (Pascals)	Energy Rating
MV4HT-287/592/292-6GD2G	M6	287	592	292	7	1700	100	E
MV4HT-492/592/292-6GD2G	M6	492	592	292	12	2500	100	E
MV4HT-592/592/292-6GD2G	M6	592	592	292	15	3400	100	E
MV4HT-287/592/292-8GD2G	F8	287	592	292	7	1700	135	C
MV4HT-492/592/292-8GD2G	F8	492	592	292	12	2500	135	C
MV4HT-592/592/292-8GD2G	F8	592	592	292	15	3400	135	C
MV4HT-305/610/400-6GD2G	M6	305	610	400	11	1700	80	C
MV4HT-490/610/400-6GD2G	M6	490	610	400	18	2500	80	C
MV4HT-610/610/400-6GD2G	M6	610	610	400	22	3400	80	C
MV4HT-305/610/400-8GD2G	F8	305	610	400	11	1700	100	B
MV4HT-490/610/400-8GD2G	F8	490	610	400	18	2500	100	B
MV4HT-610/610/400-8GD2G	F8	610	610	400	22	3400	100	B