

## MVH PLASTIC SERIES / 292mm (MAXIMUM FLOW)

EN 1822 EFFICIENCY: E10-H14  
 MEDIA : Micro Glass Fibre  
 SEPARATORS: Hotmelt  
 GASKET: Two component continuous, polyurethane  
 FINAL PRESSURE DROP: 600 Pascals  
 OPERATING TEMPERATURE: 80 °C degrees



### HIGH CAPACITY HEPA FILTERS WITH PLASTIC FRAME

Part Number	Filter Class (EN 1822)	Width (mm)	Height (mm)	Depth (mm)	Media Area (m <sup>2</sup> )	Air Flow (m <sup>3</sup> /h)	Pressure drop (Pascals)
<b>E10</b>							
MVH-305/305/292-10PKD-10m <sup>2</sup>	E10	305	305	292	10	1375	250
MVH-305/610/292-10PKD-20m <sup>2</sup>	E10	305	610	292	20	2750	250
MVH-457/610/292-10PKD-30m <sup>2</sup>	E10	457	610	292	30	4120	250
MVH-610/610/292-10PKD-40m <sup>2</sup>	E10	610	610	292	40	5500	250
<b>E11</b>							
MVH-305/305/292-11PKD-10m <sup>2</sup>	E11	305	305	292	10	1250	250
MVH-305/610/292-11PKD-20m <sup>2</sup>	E11	305	610	292	20	2500	250
MVH-457/610/292-11PKD-30m <sup>2</sup>	E11	457	610	292	30	3750	250
MVH-610/610/292-11PKD-40m <sup>2</sup>	E11	610	610	292	40	5000	250
<b>E12</b>							
MVH-305/305/292-12PKD-10m <sup>2</sup>	E12	305	305	292	10	1000	250
MVH-305/610/292-12PKD-20m <sup>2</sup>	E12	305	610	292	20	2000	250
MVH-457/610/292-12PKD-30m <sup>2</sup>	E12	457	610	292	30	3000	250
MVH-610/610/292-12PKD-40m <sup>2</sup>	E12	610	610	292	40	4000	250
<b>H13</b>							
MVH-305/305/292-13PKD-10m <sup>2</sup>	H13	305	305	292	10	1000	280
MVH-305/610/292-13PKD-20m <sup>2</sup>	H13	305	610	292	20	2000	280
MVH-457/610/292-13PKD-30m <sup>2</sup>	H13	457	610	292	30	3000	280
MVH-610/610/292-13PKD-40m <sup>2</sup>	H13	610	610	292	40	4000	280
<b>H14</b>							
MVH-305/305/292-14PKD-10m <sup>2</sup>	H14	305	305	292	10	800	280
MVH-305/610/292-14PKD-20m <sup>2</sup>	H14	305	610	292	20	1600	280
MVH-457/610/292-14PKD-30m <sup>2</sup>	H14	457	610	292	30	2400	280
MVH-610/610/292-14PKD-40m <sup>2</sup>	H14	610	610	292	40	3200	280