

MV SINGLE CELL SERIES / 65mm - 86,5mm

EN 779 EFFICIENCY: F8-F9 / H12-H13
MEDIA : Micro Glass Fibre
SEPARATORS: Hotmelt
FRAME: Heat Resistant incinerable plastic, Stainless steel, Galvanized steel, Aluminium
GASKET: Two component, continuous polyurethane
FINAL PRESSURE DROP: 450 Pascals
OPERATING TEMPERATURE: 80 °C



SINGLE CELL V FILTERS

Part Number	Filter Class (EN 779)	Width (mm)	Height (mm)	Depth (mm)	Media Area (m ²)	Air Flow (m ³ /h)	Pressure drop (Pascals)
F8 ▶							
MV-202/400/86,5-8GN	F8	400	202	86,5	2,2	135	90
MV-202/600/86,5-8GN	F8	600	202	86,5	3,2	200	90
MV-202/600/65-8GN	F8	600	202	65	3,2	200	55
F9 ▶							
MV-202/400/86,5-9GN	F9	400	202	86,5	2,2	135	130
MV-202/600/86,5-9GN	F9	600	202	86,5	3,2	200	130
MV-202/600/65-9GN	F9	600	202	65	3,2	200	85
MV-303/600/86,5-9GN	F9	600	303	86,5	5	300	130
E11 ▶							
MV-202/400/86,5-11GN	E11	400	202	86,5	2,2	135	160
MV-202/600/86,5-11GN	E11	600	202	86,5	3,2	200	160
MV-202/600/65-11GN	E11	600	202	65	3,2	200	115
E12 ▶							
MV-202/400/86,5-12GN	E12	400	202	86,5	2,2	135	170
MV-202/600/86,5-12GN	E12	600	202	86,5	3,2	200	170
MV-202/600/65-12GN	E12	600	202	65	3,2	200	125
H13 ▶							
MV-202/600/86,5-13GN	H13	600	202	86,5	3,2	200	195
MV-202/600/65-13GN	H13	600	202	65	3,2	200	145
MV-303/600/86,5-13GN	H13	600	303	86,5	5	300	195